

INKJET HOLOGRAPHIC

TECHNICAL INFORMATION

LHG/SS

Item #: IHG8511SSG 10 Sheets Media: Self adhesive film Media Type: Special Effect Color: Silver Shine /Holographic Printers: Most Desktop Inkjet Type of Adhesive: Permanent. Self Adhesive Special Effect Film

This film is not recommended for outdoor use.

1) Copy/Print on to the silver side of the media using compatible printer.

This media may NOT work in some large industrial office color copiers and/or cause damage to such equipment.

Use only in late model laser printer that has bypass tray for card stock or thick media.

- 2) To prevent a paper jam, make sure the sheet is not bent or warped or corners folded BEFORE loading. Loading by hand ONE SHEET at the time is a way to make sure it loads correctly.
- 3) When gluing this label to any surface, clean the substrate and remove residual grease, soot or dust.
- 4) It is not recommended (on larger labels) to remove all the back paper before installing. It's better to remove the paper from a small area at one end first such as a ½" vertical strip at the left hand or right hand edge.
- 5) Line up your label. When the position looks correct, let the label make contact with the surface on the edge where you removed the back paper.
- 6) Now bend the label back and carefully remove the rest of the protective back paper, and glue the label down working from the end you glued first. Then work your way towards the other end holding that end away from the surface. You can use your finger or a sponge and only press down (glue) a small area each time to prevent trapping air bubbles. Do not use excessive pressure when working the label in this way because you may smudge the ink.

To make the label scratch resistant use over laminate. Make tests before starting production for resale, using your equipment and method of printing.

If you use self adhesive media on automobiles or other items where you don't want the label to become permanent or difficult to remove after long time, then we recommend our selection of media with removable adhesive.

General: If you are working with 4.25" x 11" vinyl you can try removing all the backing material and then use the technique described above.

Disclaimer: We have tested the LHG on various substrates with good results. This user of this paper/film must however determine the suitability of this product before beginning production, using his equipment and method of application. The Sellers and Manufactures maximum obligation shall be to replace paper/film that has been found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.