



HYAZ™ Inkjet Media

Silver Self-Adhesive Polyester Film

Printing and Application Instructions

- 1) Copy/Print on to the metallic shiny side of the media using compatible Inkjet Printer.
- 2) To prevent a paper jam, make sure the film is not bent or warped or corners folded BEFORE loading. Loading by hand ONE SHEET at the time (pressing FF/Ready) is a way to make sure it loads correctly.
- 3) When gluing a the poly film to any surface, clean the surface and remove residual grease, soot or dust.
- 4) It is not recommended (on larger labels like 11" X 17") to remove all the back paper before installing. It's better to remove the paper from a small area at one end first such as a 1/2" vertical strip at the left hand or right hand edge.
- 5) Line up your label. When the position looks correct, let the label make contact with the surface on the edge where you removed the back paper.
- 6) Now bend the label back and carefully remove the rest of the protective back paper, and glue the label down working from the end you glued first. Then work your way towards the other end holding that end away from the surface. Do not use excessive pressure when working the label in this way because you may smudge the ink.
- 7) **This media in NOT recommended for outdoor use. If**

Item #	SAP8511G
Media	Self Adhesive Metallic Film
Media Type	Inkjet
Color	Silver
Printers	Most Desk Top
Type of Adhesive	Permanent.

the label is used outdoors you must use clear spray and overlaminate. The Overlaminates must be applied in such way that it prevents water from contacting the label. Clear enamel spray is available in most hardware or automotive parts stores.

You can spray the label before you apply it (after printing) to prevent over spray. Fixative spray is available in most craft stores or you can use clear spray sold in most automotive parts stores. **Use our WOL overlaminates together with the spray.** Using clear spray as the only protection will offer limited water proofing.

To extend UV resistant of Inkjet media HPS offers overlaminates with built in UV barrier.

General: If you are working with 4.25" x 11" label you can try removing all the backing material and then use the technique described above.

NOTE: If using self adhesive media, note that any adhesive may become difficult to remove over time. If you want to use self adhesive media on automobiles or other items where you don't want the label to become permanent or difficult to remove after long time, then we recommend our selection of media with removable adhesive

Printer Settings

In most cases selecting transparency and normal resolution will give the best results. Selecting photo glossy film or other media may work as well and better depending on printer used.

HPS PO Box 855
 Rhome TX 76078-0855
 sales2003@papilio.com
 www.papilio.com

For complete updated list of our media and to order on line go to www.papilio.com or call 817-489-5249

Disclaimer: We have tested our media in various personal inkjet printers with good results. The user of this paper/film must determine the suitability of this product before beginning production, using his equipment and method of application. The sellers and manufacturers maximum obligation shall be to replace paper/film that has been found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.